



NS0-593^{Q&As}

NetApp Certified Support Engineer ONTAP Specialist

Pass NetApp NS0-593 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-593.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You have a 4-node NetApp ONTAP 9.8 cluster with an AFF A400 HA pair and a FAS8300 HA pair with 16 TB NL-SAS drives. You are asked to automatically tier 150 TB of Snapshot copy data from the AFF A400 aggregates to the FAS8300.

In this scenario, which ONTAP license must be added to the cluster to accomplish this task?

- A. S3 license
- B. VE license
- C. TPM license
- D. FabricPool license

Correct Answer: C

QUESTION 2

A customer's storage administrator informs you about the deactivated Automatic Switchover (AUSO) feature on their MetroCluster IP environment. What information would you tell your customer in this scenario?

- A. The AUSO feature cannot be activated due to a non-mirrored aggregate.
- B. The AUSO feature is not available in Metrocluster IP installations by design.
- C. A faulty link automatically deactivated the AUSO feature.
- D. This is a configuration failure, you can activate that feature for the customer.

Correct Answer: A

QUESTION 3

Which two statements about NetApp Cloud Volumes ONTAP licenses are true? (Choose two.)

- A. Having an Essentials package enables you to convert to another licensing option.
- B. Capacity-based license packages support only single-node configurations.
- C. BYOL licenses are purchased directly from NetApp.
- D. AWS Marketplace contracts cannot be mixed with BYOL.

Correct Answer: BC

QUESTION 4



A customer calls you to troubleshoot a network issue. The customer wants to create a packet trace for all clients on the 192.168.9.0/24 subnet.

```
cli::> network interface show -vserver CIFS
-----
Vserver      Logical Interface  Status Admin/Oper  Network Address/Mask  Current Node  Current Port  Is Home
-----
CIFS
nfs1         nfs1         up/up      10.92.4.202/16  cli1n1  e2a-1092      true
iscsi1      iscsi1      up/up      10.91.3.132/24  cli1n1  a0a-322      true
iscsi2      iscsi2      up/up      10.95.7.114/24  cli1n1  a0a-456      true
mgmt        mgmt        up/up      10.92.6.200/16  cli1n1  e2a-1092      true
nfs2        nfs2        up/up      192.168.3.9/24  cli1n1  e2a-100      true

cli::> network route show -vserver CIFS
-----
Vserver      Destination  Gateway  Metric
-----
CIFS
0.0.0.0/0    10.92.0.1    10
0.0.0.0/0    10.92.0.2    20
10.81.50.140/32  192.168.3.254  20
192.168.9.0/24  192.168.3.254  20

5 entries were displayed.
```

Referring to the exhibit, on which interface do you have to run the packet trace?

- A. a0a-322
- B. e2a-100
- C. e2a-1092
- D. a0a-456

Correct Answer: C

QUESTION 5

The motherboard of Node-01 is being replaced. To perform this task, a takeover was Initiated from Node-02. Node-02 panics showing the string below.

PANIC; Permanent errors on all HA mailbox disks (while marshalling header) in SKprocess fnmbx_instanceWorker on release 9.5P8 (C)

What has happened in this situation?

- A. While in maintenance mode, the sldiag device show command was executed.
- B. While in maintenance mode, the fcdadmin device_map command was executed.
- C. While in maintenance mode, the HA_config show command was executed.
- D. While in maintenance mode, the mailbox destroy local command was executed.



Correct Answer: B

[Latest NS0-593 Dumps](#)

[NS0-593 Practice Test](#)

[NS0-593 Braindumps](#)