



# NS0-593<sup>Q&As</sup>

NetApp Certified Support Engineer ONTAP Specialist

## Pass NetApp NS0-593 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-593.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Your customer has deployed a two petabyte NetAppONTAP FlexGroup volume across their 4-node ONIAP 9.8 cluster. They plan to store over three billion files. They want to prevent file 10 conflicts since files are placed into the FlexGroup volume.

In this scenario, which two NFS SVM parameters should be enabled? (Choose two.)

- A. -v3-64bit-identifiers
- B. -v4-fsid-change
- C. -v3-fsid-change
- D. -v4-64bit-identifiers

Correct Answer: AC

### QUESTION 2

A system panic due to an "L2 watchdog timeout hard reset" error occurred. You have found a FIFO message in the SP log. Which FIFO message is useful for investigating this issue?

- A. before NMI BBSP:C=00 L=00 FIFO: F3 F2 F1 F0 5 B2 0 0 0 80 20 E F E3 C0 C2 3 4 6 7 9 9 A
- B. BIOS exit BBSP:C=2F L=20 FIFO: 2 C8 C9 C4 24 4 6 18 7 8 11
- C. before Reset BBSP:C=00 L=00 FIFO:
- D. ONTAP Shutdown BBSP:C=00 L=2F FIFO:

Correct Answer: B

### QUESTION 3

You receive the panic message shown in the exhibit.

```
Uncorrectable Machine Check Error at CPU0. MCO Error: STATUS<0xb200000430000800>
(Val,UnCor,Enable,PCC,ErrCode(Src,NTG,Gen,Mem,L0)). MCS Error: STATUS<0xf2000010c4300e0f>
(Val,OverF,UnCor,Enable,PCC,ErrCode(Gen,NTG,Gen,Gen)); Uncorrectable error at DIMM-1,
Channel 0, Serial: BA-00-1131-00098398169002460-I01-NTA-T1?!, FERR(0x400), NERR(0x402), MERR
M10Err, Rank 3, Bank 6, CAS 0x1e8, RAS 0x1bcf Uncorrectable error at DIMM-1, Channel 0, Serial:
BA-00-1131-00098398169002460-I01-NTA-T1?!, MERR M10Err, Rank 3, Bank 6, CAS 0x1e8, RAS 0x1bc.
```

In this scenario, which component should you troubleshoot first?

- A. the PCI card in slot 3
- B. the MetroCluster FC-VI card in slot 6
- C. the memory module in slot 1



D. the CPU

Correct Answer: D

---

#### QUESTION 4

You are deploying NetApp ONTAP Select. When trying to add VMware vCenter to the inventory, you receive the message shown below.

Credential authentication failed for x.x.x.x with: HostConnectionFailed

In this scenario, how would you correct this problem?

- A. Change the vCenter password.
- B. Change the IP address of the ONTAP Select Deploy VM.
- C. Change the gateway address of the ONTAP Select Deploy VM.
- D. Change the IP address of the vCenter server.

Correct Answer: A

---

#### QUESTION 5

A customer's storage administrator informs you about the deactivated Automatic Switchover (AUSO) feature on their MetroCluster IP environment. What information would you tell your customer in this scenario?

- A. The AUSO feature cannot be activated due to a non-mirrored aggregate.
- B. The AUSO feature is not available in Metrocluster IP installations by design.
- C. A faulty link automatically deactivated the AUSO feature.
- D. This is a configuration failure, you can activate that feature for the customer.

Correct Answer: A

[Latest NS0-593 Dumps](#)

[NS0-593 VCE Dumps](#)

[NS0-593 Practice Test](#)