



NSE7_EFW-7.0^{Q&As}

Fortinet NSE 7 - Enterprise Firewall 7.0

Pass Fortinet NSE7_EFW-7.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/nse7_efw-7-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

View the exhibit, which contains the partial output of an IKE real-time debug, and then answer the question below.

```
ike 0: comes 10.0.0.2:500-> 10.0.0.1:500, ifindex-7...
ike 0: IKEV1 exchange-Aggressive id-baf47d0988e9237f/2f405ef3952f6fda len 430
ike 0: in
BAF47D0988E9237F2F405EF3952F6FDA0110040000000000000001AE0400003C0000000100000001000000300101000
ike 0: RemoteSite:4: initiator: aggressive mode get 1st response
ike 0: RemoteSite:4: VID RFC 3947 4A131C81070358455C5728F20E95452F
ike 0: RemoteSite:4: VID DPD AFCAD71368A1F1c96B8696FC77570100
ike 0: RemoteSite:4: VID FORTIGATE 8299031757A36082C6A621DE000502D7
ike 0: RemoteSite:4: peer is FortiGate/FortiOS (v6 b932)
ike 0: RemoteSite:4: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3
ike 0: RemoteSite:4: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3C0000000
ike 0: RemoteSite:4: received peer identifier FQDN 'remote'
ike 0: RemoteSite:4: negotiation result
ike 0: RemoteSite:4: proposal id = 1:
ike 0: RemoteSite:4:     protocol id - ISAKMP:
ike 0: RemoteSite:4:     trans_id - KEY_IKE.
ike 0: RemoteSite:4:     encapsulation - IKE/none
ike 0: RemoteSite:4:     type=OAKLEY_ENCRYPT_ALG, val=AES_CBC, key-len=128
ike 0: RemoteSite:4:     type=OAKLEY_HASH_ALG, val=SHA
ike 0: RemoteSite:4:     type=AUTH_METHOD, val=PRESHARED_KEY.
ike 0: RemoteSite:4:     type=OAKLEY_GROUP, val=MODF1024.
ike 0: RemoteSite:4: ISAKMP SA lifetime=86400
ike 0: RemoteSite:4: ISAKMP SA baf47d0988e9237f/2f405ef3952f6fda key
16:B25B6C9384D8BDB24E3DA3DC90CF5E73
ike 0: RemoteSite:4: PSK authentication succeeded
ike 0: RemoteSite:4: authentication OK
ike 0: RemoteSite:4: add INITIAL-CONTACT
ike 0: RemoteSite:4: enc
BAF47D0988E9237F2F405EF3952F6FDA08100401000000000000080140000181F2E48BFD8E9D603F
ike 0: RemoteSite:4: out
BAF47D0988E9237F2F405EF3952F6FDA0810040100000000000008c2E3FC9BA061816A396F009A12
ike 0: RemoteSite:4: sent IKE msg (agg_12send) : 10.0.0.1:500 ->10.0.0.2:500, len-140, id-
baf47d0988e9237f/2
ike 0: RemoteSite:4: established IKE SA baf47d0988e9237f/2f405ef3952f6fda
```

Which statements about this debug output are correct? (Choose two.)

- A. The remote gateway IP address is 10.0.0.1.
- B. It shows a phase 1 negotiation.
- C. The negotiation is using AES128 encryption with CBC hash.
- D. The initiator has provided remote as its IPsec peer ID.

Correct Answer: BD

QUESTION 2

Two independent FortiGate HA clusters are connected to the same broadcast domain. The administrator has reported that both clusters are using the same HA virtual MAC address. This creates a duplicated MAC address problem in the



network. What HA setting must be changed in one of the HA clusters to fix the problem?

- A. Group ID.
- B. Group name.
- C. Session pickup.
- D. Gratuitous ARPs.

Correct Answer: A

https://help.fortinet.com/fos50hlp/54/Content/FortiOS/fortigate-high-availability-52/HA_failoverVMAC.htm

QUESTION 3

An administrator wants to capture encrypted phase 2 traffic between two FortiGate devices using the built-in sniffer.

If the administrator knows that there is no NAT device located between both FortiGate devices, which command should the administrator run?

- A. `diagnose sniffer packet any 'ah'`
- B. `diagnose sniffer packet any 'ip proto 50'`
- C. `diagnose sniffer packet any 'udp port 4500'`
- D. `diagnose sniffer packet any 'udp port 500'`

Correct Answer: B

Explanation: Enterprise_Firewall_7.0_Study_Guide-Online.pdf p. 443 Phase 2 : ESP => IP protocol 50

This command will capture any packets that use the IP protocol number 50, which is ESP (Encapsulating Security Payload). ESP is used to encrypt and authenticate the phase 2 traffic between two FortiGate devices1.

QUESTION 4

An administrator is running the following sniffer in a FortiGate:

```
diagnose sniffer packet any "host 10.0.2.10" 2
```

What information is included in the output of the sniffer? (Choose two.)

- A. Ethernet headers.
- B. IP payload.
- C. IP headers.
- D. Port names.

Correct Answer: BC



<https://kb.fortinet.com/kb/documentLink.do?externalID=11186>

QUESTION 5

Refer to the exhibit, which contains the output of diagnose sys session list.

```
# diagnose sys session list
session info: proto=6 proto_state=01 duration=73 expire=3597 timeout=3600
flags=00000000 sockflag=00000000 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
per_ip_shaper=
class_id=0 ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=may_dirty synced none app_atf
statistic(bytes/packets/allow_err): org=822/11/1 reply=9037/15/1 tuples=2
orgin->sink: org pre->post, reply pre->post dev=4->2/2->4
gwy=100.64.1.254/10.0.1.10
hook-post dir=org act=snat 10.0.1.10:65464->54.192.15.182:80(100.64.1.1:65464)
hook-pre dir=reply act=dnat 54.192.15.182:80->100.64.1.1:65464(10.0.1.10:65464)
pos/(before,after) 0/(0,0), 0/(0,0)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00000098 tos=ff/ff ips_view=0 app_list=0 app=0
dd_type=0 dd_mode=0
```

If the HA ID for the primary unit is zero (0), which statement about the output is true?

- A. This session cannot be synced with the slave unit.
- B. The inspection of this session has been offloaded to the slave unit.
- C. The master unit is processing this traffic.
- D. This session is for HA heartbeat traffic.

Correct Answer: C

[NSE7_EFW-7.0 PDF Dumps](#)

[NSE7_EFW-7.0 Practice Test](#)

[NSE7_EFW-7.0 Braindumps](#)